### **Environmental Protection Agency**

# NSPS FOR THE SECONDARY TIN SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Fluoride	588.000	334.300
Tin	6.384	3.696
Total suspended solids	252.000	201.600
pH	( <sup>1</sup> )	( <sup>1</sup> )

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(f) Spent electrowinning solution from municipal solid waste.

### NSPS FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of MSW scrap used as raw material	
Lead	0.033 0.024 4.165 0.045 1.785 (¹)	0.015 0.010 2.368 0.026 1.428 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(g) Tin hydroxide supernatant from scrap.

### NSPS FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of tin metal re- covered from scrap	
Lead	15.580 11.130 1,947.000 21.140 834.600 (¹)	7.233 4.451 1,107.000 12.240 667.700 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(h) Tin hydroxide supernatant from plating solutions and sludges.

# NSPS FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of tin metal re- covered from plating so- lutions and sludges	
Lead	32.20 23.00 4,025.00 43.70 1,725.00	14.95 9.20 2,289.00 25.30 1,380.00

# NSPS FOR THE SECONDARY TIN SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(i) Tin hydroxide filtrate.

### NSPS FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of tin metal pro- duced	
Lead	7.012	3.256
Cyanide (total)	5.009	2.004
Fluoride	876.500	498.400
Tin	9.517	5.510
Total suspended solids	375.700	300.500
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

# § 421.295 Pretreatment standards for existing sources.

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources. The mass of wastewater pollutants in secondary tin process wastewater introduced into a POTW must not exceed the following values:

(a) Tin smelter SO<sub>2</sub> scrubber.

### PSES FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of crude tapped tin produced	
Arsenic	12.790	5.703
Lead	2.575	1.196
Iron	11.040	5.611
<u>Tin</u>	3.495	2.024

(b) Dealuminizing rinse.

## §421.296

# PSES FOR THE SECONDARY TIN SUBCATEGORY PS

## PSES FOR THE SECONDARY TIN SUBCATEGORY

40 CFR Ch. I (7-1-08 Edition)

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of dealuminized scrap produced	
Lead	0.010 0.007 1.225 0.013	0.005 0.003 0.697 0.008

(c) Tin mud acid neutralization filtrate.

### PSES FOR THE SECONDARY TIN SUBCATEGORY

Maximum for any 1 day	Maximum for monthly average
mg/kg (pounds per million pounds) of neutralized dewatered tin mud pro- duced	
1.413 1.009 176.600 1.918	0.656 0.404 100.400 1.110
	mg/kg (pound pounds) of dewatered duced  1.413 1.009 176.600

(d) Tin hydroxide wash.

### PSES FOR THE SECONDARY TIN SUBCATEGORY

Maximum for any 1 day	Maximum for monthly average
mg/kg (pounds per million pounds) of tin hydroxide washed	
3.347 2.391 418.400 4.542	1.554 0.956 237.900 2.630
	for any 1 day mg/kg (pound pounds) of washed 3.347 2.391 418.400

(e) Spent electrowinning solution from new scrap.

# PSES FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cathode tin produced	
Lead	4.704	2.184
Cyanide (total)	3.360	1.344
Fluoride	588.000	334.300
Tin	6.384	3.696

(f) Spent electrowinning solution from municipal solid waste.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of MSW scrap used as raw material	
Lead	0.033 0.024 4.165 0.045	0.015 0.010 2.368 0.026

(g) Tin hydroxide supernatant from scrap.

### PSES FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of tin metal re- covered from scrap	
Lead	15.580 11.130 1,947.000 21.140	7.233 4.451 1,107.000 12.240

(h) Tin hydroxide supernatant from plating solutions and sludges.

# PSES FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of tin metal re- covered from plating so- lutions and sludges	
Lead	32.20 23.00 4,025.00 43.70	14.95 9.20 2,289.00 25.30

(i) Tin hydroxide filtrate.

# PSES FOR THE SECONDARY TIN SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of tin metal pro- duced	
Lead	7.012 5.009 876.500 9.517	3.256 2.004 498.400 5.510

# § 421.296 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart